



CONCRETE PIPE 2021 SOUTHERN ALBERTA



Index

CONCRETE PIPE	
Dimensions	2
Pipe Class Estimation Table	3
Standard Installation Beddings	4
Concrete Pipe Design Methods	5
Curved Alignment / Bends	6
Flared Ends / Outfalls	7
T-Riser Manholes	8
Jacking Pipe	9
Microtunneling Pipe	10
BOX CULVERT	12
CATCH BASINS	14
MANHOLES	
Type 5A Manholes	16
Estimating Guide	18
Check Valve Manholes	19
1S Manhole/Life Station	20
1S Manhole - Pipe Angle Entry	21
LARGE DIAMETER MANHOLE / LIFT STATIONS	22
BIG BOX MANHOLES	24
MULTI PANEL VAULT	26
STORMCEPTOR & STORMTRAP	
Stormceptor	28
Jellyfish	31
Stormtrap	32
PERFORMANCE MONITORING	34
@SOURCE-ENERGY GEOTHERMAL ENERGY CAPTURE PIPE	36
STONE STRONG RETAINING WALL	37
HANDLING AND INSTALLATION	39

Contacts

SALES:


Ashik Ramdass
ashik.ramdass@lafargeholcim.com
(403) 899-3497

STORMTRAP & STORMCEPTOR:


Gerald Huizer
gerald.huizer@lafargeholcim.com
(1403) 707-6091

CONCRETE PIPE - DIMENSIONS

Nominal Inside Diameter		Wall	Pipe Style	Lifting Clutches Required (Ton)	Weight		Dimensions (mm)				
mm	in				kg/piece	kg/m	Pipe ID	Pipe OD	Bell OD	Wall Thickness	Spigot Length
300	12	C	Bell	-	525	215	305	445	508	70	92
375	15	C	Bell	-	700	287	381	533	610	76	92
450	18	B	Bell	-	750	307	457	585	711	64	92
525	21	C	Bell	-	1125	461	533	711	806	89	98
600	24	C	Bell	2	1375	564	610	800	902	95	98
675	27	C	Bell	2	1650	676	686	889	1006	102	102
750	30	C	Bell	2	1950	799	762	978	1099	108	102
750	30	X	Straight	4	2875	1178	762	1085	-	162	102
900	36	C	Bell	4	2625	1076	914	1156	1302	121	102
900	36	X	Bell	4	2775	1137	914	1188	1302	137	102
1050	42	C	Bell	4	3275	1342	1067	1334	1461	133	108
1050	42	X	Straight	4	4525	1855	1067	1442	-	187	108
1200	48	B	Straight	4	3300	1352	1219	1473	-	127	102
1200	48	C	Straight	4	3825	1568	1219	1511	-	146	102
1350	54	B	Straight	4	4050	1660	1372	1652	-	140	127
1500	60	C	Straight	4	5575	2285	1524	1866	-	171	127
1650	66	B	Straight	4	5850	2398	1676	2006	-	165	127
1650	66	C	Straight	4	6575	2695	1676	2044	-	184	127
1800	72	B	Straight	8	6850	2807	1829	2185	-	178	127
1800	72	C	Straight	8	7625	3125	1829	2223	-	197	127
1950	78	C	Straight	8	8800	3607	1981	2401	-	210	140
2100	84	B	Straight	8	9100	3730	2134	2540	-	203	143
2400	96	C	Straight	8	12775	5236	2438	2934	-	248	127
2700	108	C	Straight	20	15800	6475	2743	3289	-	273	127
3000	120	B	Straight	20	17800	7295	3048	3606	-	279	152



a) Bell Type Concrete Pipe
PIPE I.D. Ranging 300mm diameter to 1050 diameter



b) Straight/Jacking Concrete Pipe
1200 mm diameter and larger

CONCRETE PIPE - CLASS ESTIMATION TABLE

Pipe Diameter (mm)	Installation Type	Maximum Depth to Invert (m) for:			
		Class II	Class III	Class IV	Class V
300	1				14.9
	2				10.5
	3				8.2
	4				5.4
375	1				15.4
	2				10.8
	3				8.5
	4				5.7
450	1				15.7
	2				11.0
	3				8.7
	4				5.9
525	1				15.9
	2				11.1
	3				8.9
	4				6.1
600	1			11.6	16.0
	2			8.1	11.2
	3			6.5	9.0
	4			4.5	6.2
675	1			11.6	16.1
	2			8.2	11.3
	3			6.6	9.1
	4			4.6	6.5
750	1			11.6	16.1
	2			8.2	11.3
	3			6.6	9.1
	4			4.6	6.5
900	1		7.8	11.7	16.1
	2		5.5	8.3	11.4
	3		4.4	6.7	9.2
	4		3.1	4.9	6.7
1050	1	6.2	7.9	11.8	16.3
	2	4.4	5.7	8.5	11.6
	3	3.5	4.5	6.8	9.3
	4		3.2	5.0	6.9
1200	1	6.3	8.0	11.9	16.3
	2	4.6	5.8	8.6	11.8
	3	3.6	4.7	7.0	9.5
	4		3.4	5.2	7.0


Pipe Diameter (mm)	Installation Type	Maximum Depth to Invert (m) for:			
		Class II	Class III	Class IV	Class V
1350	1	6.4	8.1	12.0	16.7
	2	4.7	5.9	8.7	11.9
	3	3.7	4.8	7.1	9.6
	4		3.5	5.3	7.2
1500	1	6.5	8.2	12.1	16.5
	2	4.8	6.0	8.8	12.0
	3	3.8	4.9	7.1	9.6
	4		3.6	5.5	7.3
1650	1	6.6	8.3	12.1	16.5
	2	4.9	6.1	8.9	12.1
	3	3.8	5.0	7.3	9.7
	4		3.7	5.6	7.5
1800	1	6.6	8.3	12.2	16.6
	2	4.9	6.2	9.0	12.2
	3	3.9	5.0	7.3	9.8
	4		3.7	5.7	7.6
1950	1	6.7	8.4	12.3	16.7
	2	5.1	6.4	9.2	12.3
	3	4.0	5.2	7.5	10.0
	4		3.9	5.8	7.8
2100	1	6.8	8.5	12.4	16.8
	2	5.2	6.5	9.3	12.4
	3	4.0	5.3	7.6	10.1
	4			6.0	7.9
2400	1	7.0	8.7	12.5	16.9
	2	5.4	6.7	9.5	12.7
	3		5.5	7.8	10.3
	4			6.2	8.1
2700	1	7.2	8.9	12.7	17.0
	2	5.6	6.9	9.8	13.0
	3		5.7	8.1	10.6
	4			6.4	8.4
3000	1	7.4	9.1	12.9	17.2
	2	5.8	7.2	10.0	13.2
	3		5.9	8.3	10.8
	4			6.7	8.6

NOTES:

1. Above tables are based on recommended loadings and calculations for the “Standard Practice for the Design and Installation of Rigid Gravity Sewer Pipe in the City of Calgary”. This table is provided for convenience, but is not intended to replace proper engineering design.
2. Minimum cover for Class IV and V pipe is 0.3m. Call for shallow designs for lower classes.
3. Design assistance available to suit installation conditions.
4. Type 1 installations require prior approval from the City of Calgary for Calgary based projects.

STANDARD INSTALLATION BEDDINGS

Standard Trench Installation (Ref: ACPA)



Note 1: Clearance between pipe and trench wall shall be adequate to enable specific compaction, but not less than $D_o/6$.

Installation Type	Bedding Thickness	Haunch and Outer Bedding	Lower Side
Type 1	$D_o/24$ minimum; not less than 3 in. If rock foundation, use $D_o/12$ minimum; not less than 6 in.	95% Category I	Undisturbed natural soil with firmness equivalent to the following placed soils: 90% Category I, 95% Category II, or 100% Category III, or embankment to use the same materials
Type 2	$D_o/24$ minimum; not less than 3 in. If rock foundation, use $D_o/12$ minimum; not less than 6 in.	90% Category I or 95% Category II	Undisturbed natural soil with firmness equivalent to the following placed soils: 85% Category I, 90% Category II, or 95% Category III, or embankment to the same requirements.
Type 3	$D_o/24$ minimum; not less than 3 in. If rock foundation, use $D_o/12$ minimum; not less than 6 in.	85% Category I, 90% Category II, or 95% Category III	Undisturbed natural soil with firmness equivalent to the following placed soils: 85% Category I, 90% Category II, or 95% Category III, or embankment to the same requirements.
Type 4	No bedding required, except if rock foundation, use $D_o/12$ minimum; not less than 6 in.	No compaction required, except if Category III, use 85% Category III	No compaction required, except if Category III, use 85% Category III

Pipe design in the City of Calgary and most major municipalities is based on Standard Installation Beddings, which outline four standard installation types. Type 1 installations represent the most compact soil material, while Type 4 installations represent poor soil material. Type 2 installations are generally considered the most common method. A generalized depiction of a standard installation for concrete pipe is presented below.

- NOTES:**
1. Category I (Gravelly Sand) includes SW, SP, GW, GP
 2. Category II (Sandy Silt) includes GM, SM, ML. Also, GC, SC with less than 20% assing #200 Sieve
 3. Category III (Silty Clay) includes CL, MH, GC, SC, CH

CONCRETE PIPE DESIGN METHODS

INDIRECT DESIGN (Standard Class Pipe)

Indirect design provides a convenient and consistent method for designers, manufacturers and inspectors to simply select from a fill-height table, as indicated in Page 3. The reinforcement is designed in accordance to ASTM C76, and the pipe strength is verified by the D-Load (three-edge bearing) test relative to the 0.01 inch crack and ultimate loading values.

DIRECT DESIGN (Standard Installation Direct Design - SIDD)

The SIDD method is typically considered when the pipe depth is beyond or above the cover indicated in the fill height table. Moreover, some specific pipe classes fall within a wide range of cover and the SIDD method can be selected for specific depths for potential cost savings.




CURVED ALIGNMENT

Nominal Inside Diameter (mm)		12.5mm Joint Opening		12.5mm Joint Opening and 12.5mm Bevel		Pipe Bends	
		Minimum Radius (m)	Deflection Angle per Joint (Degrees)	Minimum Radius (m)	Deflection Angle per Joint (Degrees)	Weight kg/piece	Approximate Lay Length
300	C	81	1.61	-	-	263	1.22
375	C	98	1.34	-	-	350	1.22
450	B	116	1.21	-	-	375	1.22
525	C	139	1.01	-	-	563	1.22
600	C	156	0.90	-	-	688	1.22
675	C	174	0.81	87	1.61	1650	2.44
750	C	191	0.73	96	1.46	1950	2.44
900	C	226	0.62	113	1.24	2625	2.44
1050	C	261	0.54	130	1.07	3275	2.44
1200	B	288	0.49	144	0.97	3300	2.44
1200	C	295	0.48	148	0.96	3825	2.44
1350	B	323	0.43	162	0.87	4050	2.44
1500	C	357	0.39	179	0.78	5575	2.44
1650	B	392	0.36	196	0.71	5850	2.44
1650	C	400	0.35	200	0.70	6575	2.44
1800	B	427	0.33	214	0.66	6850	2.44
1800	C	434	0.32	217	0.64	7625	2.44
1950	C	469	0.30	234	0.60	8800	2.44
2100	B	496	0.28	249	0.56	9100	2.44
2400	C	566	0.24	284	0.49	12775	2.44
2700	C	643	0.22	321	0.44	15800	2.44
3000	B	705	0.20	353	0.40	15350	2.10

NOTES:


1. If the specified radius is smaller than shown, bends and/or manholes will be required to meet the required alignment.
2. Bends are custom manufactured to meet required angle.
3. Beveled pipe are not available in pipe sizes 300-600mm.




FLARED ENDS/OUTFALLS

Nominal Dia. (mm)	Weight kg/pc	Dimensions (mm)						
		A	B	C		L		W
				Spigot	Bell	Spigot	Bell	
300	250	186	610	1465	1455	2075	2065	600
450	460	305	685	550	550	1235	1235	914
525	1135	240	890	965	875	1855	1765	1067
600	710	255	1055	725	725	1780	1780	1200
750	1100	305	1395	530	445	1925	1840	1535
900	1865	380	1625	845	1015	2470	2640	1820
1050	2760	535	1670	780	1050	2450	2720	1980
1200	3000	650	1775	875	875	2650	2650	2100
1350	3690	685	1665	895	895	2545	2560	2545
1500	4010	760	1525	820	925	2345	2425	2740

- NOTES:**
1. Spigot end required for inlet, bell end for outlet.
 2. No volume discount on bar screens.
 3. Outfalls for other sizes available. Call for options.




PROFILE




T-RISER

Nominal Inside Diameter		Wall Designation	Approximate Effective Height	Weight kg/piece
mm	in			
1050	42	C	1237	3700
1200	48	B	1618	3725
1200	48	C	1599	4250
1350	54	B	1770	4735
1500	60	C	1904	6065
1650	66	B	2075	6335
1650	66	C	2056	7000
1800	72	B	2227	7275
1800	72	C	2208	8050
1950	78	C	2496	9225
2100	84	B	2642	9525
2400	96	C	2991	13200
2700	108	C	3321	16225
3000	120	B	3632	18200




PROFILE




JACKING PIPE

Jacking Pipe



- 1. Steel Band
- 2. Reinforcing
- 3. Jacking Cushion
- 4. Single Offset Spigot
- 5. Lube or Grout Port



Jacking pipe is available in all straight wall pipe sizes.
See dimensions for straight wall pipe on page 2.



MICROTUNNELING PIPE





Normal Diameter	ID	OD	Wall Thickness	Effective Length	Weight (kg)
1200	1220	1490	135	3000	4350
1500	1524	1866	171	3000	6850
1800	1830	2224	197	3000	9400
2500	2500	2980	240	3000	15500
3000	3000	3600	300	2500	19500

Lafarge can produce concrete pipe in a VARIETY of sizes for trenchless installation with the jacking or tunneling methods. The pipe sections are designed for the additional axial force encountered in these operations and can be produced with ports for grout or lubrication.



MICROTUNNELING PIPE




CONCRETE BOX

Precast concrete box sections are designed to meet job specific requirements and are manufactured under factory controlled conditions. Precast box sections are the logical solution to problems of restricted head room, minimum cover, limited trench width or excessive over fills, and can be designed for jacking under roads without traffic interruption.

Concrete box sections can be used in a variety of applications to meet the needs of your project beyond the conveyance of storm water, industrial waste and sanitary sewage. Innovative product solutions include:

- Highway bridge culverts
- Stormwater retention tanks
- Rural bridge applications
- Vertical vaults
- Rip-rap lined culverts for fish crossing
- Utility corridors or pedestrian tunnel crossings



Box Size Span x Rise	Standard Length	Side Wall Thickness	Top Wall Thickness	Bottom Wall Thickness	Haunch Length	Plug/Top/Base Slab Thickness	Approximate Storage Volume (m ³)
1200 x 600	2000	125	190	150	125	300	1.35
1200 x 900	2000	125	190	150	125	300	2.05
1800 x 1200	2000	175	200	175	175	300	4.15
2400 x 1200	2000	225	215	215	200	300	5.60
<i>2400 x 1800</i>	<i>2000</i>	<i>200</i>	<i>200</i>	<i>200</i>	<i>250</i>	<i>300</i>	<i>8.35</i>
<i>2440 x 2440</i>	<i>2440</i>	<i>200</i>	<i>200</i>	<i>200</i>	<i>200</i>	<i>300</i>	<i>14.30</i>
<i>3000 x 2400</i>	<i>2000</i>	<i>250</i>	<i>250</i>	<i>250</i>	<i>250</i>	<i>300</i>	<i>14.15</i>

- NOTES:**
1. Shorter standard lengths are available for all box sizes with the exception of those highlighted in italics in the table above.
 2. For box sizes up to 6m rise and span, refer to Big Box section for details.
 3. Box lengths can be shortened, but not extended.

CONCRETE BOX

Span x Rise x Length	Item Description	Weight (kgs) Per Piece	Lift Clutches Required (Ton)
1200 X 600 2.0m Long	Culvert	3375	4
	Plug/Cap	1350/1150	
	Bend	3375	
	Sloped/Outfall End	2430	
1200 X 900 2.0m Long	Culvert	3750	4
	Plug/Cap	1800/1500	
	Bend	3750	
	Sloped/Outfall End	2700	
1800 X 1200 2.0m Long	Culvert	6450	8
	Plug/Cap	3500/2800	
	Bend	6450	
	Sloped/Outfall End	4635	
2400 X 1200 2.0m Long	Culvert	9250	8
	Plug/Cap	4850/3750	
	Bend	9250	
	Sloped/Outfall End	6050	
2400 X 1800 2.0m Long	Culvert	9825	8
	Plug/Cap	6125/4925	
	Bend	9825	
	Sloped/Outfall End	6915	
2440 X 2440 2.44m Long	Culvert	13375	20
	Plug/Cap	8550/6400	8
	Bend	13375	20
	Sloped/Outfall End	9630	20
3000 x 2400 2.0m Long	Culvert	15650	20
	Plug/Cap	11950/9375	8
	Bend	15650	20
	Sloped/Outfall End	11070	20


Cover Range:
1.0m - 3.0m
3.0m - 7.0m
0.0m - 1.0 & 7.0m - 10.0m

NOTES:

- Prices are based on standard applications designed to ASCE26-97 for a Type B1 installation and produced to ASTM C1433, CHBDC and other designs available upon request.
- See Large Manhole section for pricing of vertically installed boxes (Manhole).
- Monolithic end pieces are available upon request.
- Rough pipe openings and manhole openings available at an additional cost.
- Additional Box sizes ranging up to 6m internal span are available. See Big Box section for additional information.


CATCHBASINCOMPONENTS

Catch basin is a chamber or sump usually built at the curb which separates debris and allows surface water runoff to enter the stormwater conveyance system.




SEPARATE BASE CATCHBASIN


WEEPER HOLES
(75mm DIA)
only incl. in 1067 tall Barrel and ML09001080 xxx




MONOLITHIC BASE CATCHBASIN




DEPTH= 130 - 120mm
SLOPED BACK TOWARDS CURB
FOR C OR K1 FRAME AND GRATE
SQUARE CURB



DEPTH= 130 - 120mm
SLOPED BACK TOWARDS CURB
FOR C OR K2 FRAME AND GRATE
ROLLED CURB



DEPTH= 150mm
FOR MANHOLE FRAME AND COVER
AREA DRAIN OR SOLID TOP COVER



DEPTH= 150mm
FOR K3 FRAME AND GRATE
AREA DRAIN



CATCHBASIN MATERIALS

	Item	Description	Lifting Clutches (Ton)	Weight kg/pc
Bases 914 mm ID	Monolithic Catch Basin 1080 mm High Complete with Benched Base and 4 Weeping Holes	Up to 300 mm pipe. Complete with Gasket for SDR 35 or rough opening	4	1425
	Twin Upstream Monolithic Catch Basin Complete with Higher Benching 1080 mm High	Complete with Gasket for SDR 35	4	1425
	Monolithic Catch Basin 1200 mm High Flat Bottom	Up to 300 mm pipe. Complete with Gasket for SDR 35 or rough opening	4	1750
	Monolithic Catch Basin 1080 tall Flat Bottom with Sump (Red Deer or Airdrie Spec)	Up to 300 mm pipe. Complete w/ gasket for SDR 35 or rough opening.	4	1395
	Shallow Monolithic Catch Basin 406 mm High Complete with Benched Base	Up to 300 mm pipe. Complete with Gasket for SDR 35 or rough opening	4	715
	Flat CB Base	914 ID x 152 Deep Base	4	405
Barrels 914 mm ID	1067 mm High w/ Weeper holes	914 ID x 1067 High (36" x 42") With 4 Weeper Holes	4	865
	914 mm High	914 ID x 914 High (36" x 36")	4	740
	762 mm High	914 ID x 762 High (36" x 30")	4	615
	610 mm High	914 ID x 610 High (36" x 24")	4	495
	457 mm High	914 ID x 457 High (36" x 18")	4	370
	305 mm High	914 ID x 305 High (36" x 12")	4	250
	152 mm High	914 ID x 152 High (36" x 6")	4	125
Tops & Collars	C Top	Square Curb (Tee Top) Opening	4	345
	K2 Top	Rolled Curb Opening	4	325
	K3 Top	Rectangular Opening	4	285
	M Top	Circular Opening	4	285
	K3 Collar	K3 Top/C Top Collar - 67mm High		40
	Stormback Collar	C Top Side Inlet Collar - 67mm High		30
Frame & Covers	City of Calgary Frame and Cover/Grate	152 mm High Frame or Slotted Grate		150
	'C' Frame and Grate	C Top Rectangular Frame C Top Rectangular Inlet Grate C Top Side Inlet Grate		150
	'K2' Frame and Grate To fit Rolled Curb	K2 Top Rectangular Frame K2 Top Rectangular Grate		210
	'K3' Frame and Grate	K3 Top Rectangular Frame K3 Top Rectangular Grate		85


FOR CATCHBASIN PRICING, PLEASE EMAIL: ashik.ramdass@lafargeholcim.com

NOTES:


1. Pre-benching is for dead ends only.
2. Barrels, Flat Catch basin Base, Type M and K3 Top Slabs have a 25mm joint lip. Monolithic CBs, Type C and K2 Top slabs have a flat joint.
3. City of Calgary Sump Catch basins available upon request.

5A MANHOLE-COMPONENTS

Lafarge produces 5A manholes with 1220mm (48") internal diameter. The boot-style gasket clamps onto the pipe, reducing infiltration and exfiltration. For ribbed pipe, a straight wall adaptor is recommended to maintain the integrity of the seal, as per project specifications.



ROUND PRE-BENCHED MANHOLE BASE



FLAT BASE (ALTERNATE TO PREBENCHED BASE)

5A MANHOLE COMPONENTS

ASTM C478, CSA A257.4

	Item	Description	Lifting Clutches (Ton)	Weight kg/pc
Bases 1220 mm ID/813 mm High	100/150 mm	Maximum Pipe size of 150mm (6")	4	1960
	Prebench 200 mm	Maximum Pipe size of 200mm (8")	4	1960
	Prebench 250 mm	Maximum Pipe size of 250mm (10")	4	1960
	Prebench 300 mm	Maximum Pipe size of 300mm (12")	4	1960
	Prebench 375 mm	Maximum Pipe size of 375mm (15")	4	1960
	Prebench 450 mm	Maximum Pipe size of 450mm (18")	4	1960
	Prebench 525 mm	Maximum Pipe size of 525mm (21")	4	1960
	Prebench 600 mm	Maximum Pipe size of 600mm (24") See notes 2 & 3	4	2020
	Prebench Cul-De-Sac	4 or more openings	4	1960
	Flat Mono Base	Monolithic Flat Base (710 tall)	4	1670
Barrels & Adapters 1220 mm ID	Flat Base	1220 ID Round x 254 mm Deep Base	4	1020
	2440 mm High	Spigot up or Bell up- 6 Steps	4	3300
	1220 mm High	Spigot up or Bell up- 3 Steps	4	1650
	813 mm High	Spigot up or Bell up- 2 Steps	4	1100
	406 mm High	Spigot up or Bell up- 1 Step	4	550
	305 mm High	Spigot up or Bell up- 1 Step	4	425
	914 mm High Perforated	914 mm High Perforated Barrel	4	705
	305 mm High Spigot to Spigot Adaptor	Spigot-Spigot Adapter c/w 1 Step	4	525
	508 mm High Bell to Bell Adaptor	Bell-Bell Adapter c/w 1 Step	4	530
	Top Slab & Collars	STD Top Slab	1220 ID x 178 Deep with 710 Dia. Offset Opening	4
"C" Top Slab		1220 ID x 178 Deep with Opening for 'C' Frame and Grate	4	630
Red Deer Top Slab		1220 ID x 178 Deep with 640 Dia. Offset Opening	4	630
203 mm MH Collar		710 ID x 203 High c/w MH Step Recesses for Step-G	Hooks	205
152 mm MH Collar		710 ID x 152 High c/w MH Step Recesses for Step-G	Hooks	155
101 mm MH Collar		710 ID x 101 High c/w MH Step Recesses for Step-G	Hooks	105
75mm MH Collar		710 ID x 76 High c/w MH Step Recesses for Step-G		75
50 mm MH Collar		710 ID x 50 High c/w MH Step Recesses for Step-G		50
Accessories	City of Calgary Frame and Cover/Grate	600 mm dia x 152 mm High Frame 600 mm dia x 254 mm High Frame Solid Cover (weight/price included with Frame) Slotted Grate (weight/price included with Frame)		150 170
	Town and Country Style Frame and Cover/Grate	T&C 570 mm dia x 152mm High Frame T&CSolidCover (weight/price included with Frame) T&C Slotted Grate (weight/price included with Frame)		190
	Aluminum Step	300mm Wide Ladder Rung - Install in Barrels with 25mm Dia. Drilled Hole		
	Aluminum Poly Step	300mm Wide Poly Coated Ladder Rung - Install in Barrels with 25mm Dia. Drilled Hole		
	Galvanized Step	300mm Wide Ladder Rung - Install in Collars in Step Recess		
	Gasket	Super Seal - 1220mm ID Manhole Gasket		

FOR MANHOLE PRICING, PLEASE EMAIL: ashik.ramdass@lafargeholcim.com

NOTES:

1. Prebentched bases are made to order. Approved drawings or manhole order forms required for manufacture.
2. Standard Prebench height from invert to shoulder - 711mm, with the exception of Prebench with 600mm concrete pipe - 811mm.
3. Prebench manhole comes complete with cast in place gaskets for connection to SDR 35 PVC pipe. Other pipe styles are supplied with oversized openings.
4. In areas with high groundwater, manhole gaskets and 2440mm high Manhole Barrels are recommended.
5. All Manhole material designed to meet City of Calgary specifications. Please advise if other requirements are necessary.
6. Nitrile boot gaskets available for 200-600mm. Allow 4-5 weeks for delivery time. Please call for pricing.

ESTIMATING GUIDE for 1200mm Diameter Type 5A Manholes

CHECK VALVE
MANHOLE

Depth to Lo rest invert (m)	Prebenched Base		Manhole Barrels			Top Slab		Collars		150mm Frame & Cover
	720	1220	813	406	305	280	203	152	101	
2.00	1			1	1	1		1		1
2.10	1			1	1	1		1	1	1
2.20	1		1			1	1			1
2.30	1		1			1		2		1
2.40	1		1		1	1		1		1
2.50	1		1	1		1		1		1
2.60	1		1	1		1		1	1	1
2.70	1		1	1		1		2		1
2.80	1	1			1	1			1	1
2.90	1	1		1		1			1	1
3.00	1	1		1		1	1			1
3.10	1	1			2	1			1	1
3.20	1	1		1	1	1			1	1
3.30	1	1	1			1			1	1
3.40	1	1	1			1	1			1
3.50	1	1	1			1		2		1
3.60	1	1	1		1	1			1	1
3.70	1	1	1	1		1			1	1
3.80	1	1	1	1		1	1			1
3.90	1	1	1	1		1		2		1
4.00	1	2			1	1			1	1
4.10	1	2		1		1			1	1
4.20	1	2		1		1	1			1
4.30	1	2			2	1			1	1
4.40	1	2		1	1	1			1	1
4.50	1	2	1			1			1	1
4.60	1	2	1			1	1			1
4.70	1	2	1			1		2		1
4.80	1	2	1		1	1			1	1
4.90	1	2	1	1		1			1	1
5.00	1	2	1	1		1	1			1
5.10	1	2	1	1		1		2		1
5.20	1	3			1	1			1	1
5.30	1	3		1		1			1	1
5.40	1	3		1		1	1			1
5.50	1	3			2	1			1	1
5.60	1	3			2	1	1			1
5.70	1	3		1	1	1	1			1
5.80	1	3	1			1		1		1
5.90	1	3	1			1		1	1	1
6.00	1	3	1		1	1			1	1


CHECK VALVE MANHOLES & MISC. MATERIALS

Check Valve Manholes



Nominal Pipe Size (mm)	Manhole Type	Weight (kg/piece)
150	1200 dia. Monolithic base	2200
200	1200 dia. Monolithic base	2200
250	1.5m Type 1-S	8880
300	1.5m Type 1-S	8880
400	1.9m Type 1-S	12250

NOTES: 1. Distance from invert to base - 450mm.

ROUND CHECK VALVE



I-S CHECK VALVE



Miscellaneous Material

	Description	Price (Each) No Discount
Concrete, Cement Products, Gaskets & Lube	Wooden Pallets	\$40
	Kalicrote - Type HS (formerly Type 50) Cement 20kg bag	\$50
	Patching Cement Compound 20kg bag	\$65
	1200 Dia. Manhole Barrel Gaskets	\$65
	25mm Thick Mastic Coil Gasket 4.4m long	\$65
	Gasket Lubricant 3.5kg pail	\$85
Lifting	Subaqueous Gasket Lubricant (underwater use) 3.5kg pail	\$100
	Pair of 2 Ton Clutches (Final Sale)	\$570
	Pair of 4 Ton Clutches (Final Sale)	\$640
	Pair of 8 Ton Clutches (Final Sale)	\$1,280
Others	Pair of 20 Ton Clutches (Final Sale)	\$3,610
	Safety Platforms for manholes	Call
	Hatches	Call
	Dunnage	Call

1-S MANHOLE/LIFT STATION - DIMENSION & PRICE

	Description	For Pipe Sizes up to (mm)	Weight (kg) (Half Structure)	Dimension						
				A	B	C	D	E	F	G
1.2 1-S	Top & Bottom Half 1990 High	900	3420	175	980	1010	200	150	1200	1500
	1000 High Intermediate	-	2080	-	1000	-	-	150	1200	1500
	Top Half 980 High	675	3420	175	980	-	-	150	1200	1500
	Bottom Half 1010 High	675	3420	-	-	1010	200	150	1200	1500
	Flat Base Slab	-	1530	-	-	-	300	-	-	1500
	Skimming Manhole (Top & Bottom Half)	-	2950	175	1160	-	200	150	1200	1500
1.5 1-S	Top & Bottom Half 1990 High	1050	4440	175	1010	-	200	150	1500	1800
	1000 High Intermediate	-	2535	-	1000	-	-	150	1500	1800
	Top Half 980 High	675	4440	175	980	-	-	150	1500	1800
	Bottom Half 1010 High	675	4440	-	-	1010	200	150	1500	1800
	Flat Base Slab	-	2520	-	-	-	300	-	-	1800
	Skimming Manhole (Top & Bottom Half)	-	5015	175	1160	-	200	150	1500	1800
1.9 1-S	Top & Bottom Half 1990 High	1500	6125	200	980	1010	200	150	1930	2230
	1000 High Intermediate	-	3200	-	1000	-	-	150	1930	2230
	Top Half 980 High	675	6125	200	980	-	200	150	1930	2230
	Bottom Half 1010 High	675	6125	-	-	1010	200	150	1930	2230
	Flat Base Slab	-	3860	-	-	-	300	-	-	2230
	Skimming Manhole (Top & Bottom Half)	-	6915	200	1160	-	200	150	1930	2230
2.4 1-S	Top & Bottom Half 2405 High	1800	13000	250	1180	1225	250	230	2400	2860
	1000 High Intermediate	-	6200	-	1000	-	-	230	2400	2860
	1750 High Intermediate	-	10740	-	1750	-	-	230	2400	2860
	Top Half 1180 High	900	13000	250	1180	-	250	230	2400	2860
	Bottom Half 1225 High	-	13000	-	-	1225	-	230	2400	2860
	Flat Base Slab	-	6340	-	-	-	300	-	-	2860
2.8 1-S	Top & Bottom Half 2805 High	2100	17265	250	1380	1425	250	230	2800	3260
	1000 High Intermediate	-	7143	250	1000	-	-	230	2800	3260
	1750 High Intermediate	-	12370	-	1750	-	-	230	2800	3260
	Top Half 1380 High	1050	17265	250	1380	-	250	230	2800	3260
	Bottom Half 1425 High	-	17265	-	-	1425	-	230	2800	3260
	Flat Base Slab	-	8240	-	-	-	300	-	-	3260
Skimming Manhole (Top & Bottom Half)	-	17265	250	1400	-	250	230	2800	3260	


4.0 x 3.0 1S manhole - Contact sales for details.

NOTES:



- Standard depth of cover is 5 meters
- Use intermediate sections between top and bottom sections of 1-S Manhole to meet drop manhole invert requirements.
- Mastic gaskets (see page 17) are available for 1-S Manhole joints. Additional measures by contractor may be necessary if a watertight joint is required.
- Top and bottom half wall taper is from the thickest point at top/base slab to the center (dimension 'E'), including haunches in corners. This may affect mounting of equipment, gates, etc.

1-S MANHOLE-PIPE ANGLE ENTRY

Pipe Size (mm)	Maximum Angle for Type 1-S Manhole Size:				
	1200mm	1500mm	1930mm	2400mm	2800mm
300	45	45	45	45	45
375	45	45	45	45	45
450	45	45	45	45	45
525	40	45	45	45	45
600	35	45	45	45	45
675	30	45	45	45	45
750	25	40	45	45	45
900	0	30	45	45	45
1050	-	15	40	45	45
1200	-	-	30	45	45
1350	-	-	20	40	45
1500	-	-	10	30	40
1650	-	-	-	25	35
1800	-	-	-	10	30
1950	-	-	-	-	20
2100	-	-	-	-	15



PLAN VIEW



TYPE 5A MH MATERIAL TO FINAL GRADE

TOP HALF

INTERMEDIATE SECTION (IF REQUIRED)

BOTTOM HALF

LARGE DIAMETER MANHOLE/LIFT STATION

Lafarge provides precast large diameter round manhole (from 1500 to 3000 mm ID), and rectangular/square sections in a 1200x1200 ID. The applications of these structures are mainly for manholes with bigger inlet/outlet pipes, lift stations/pump stations, and control structures.



LARGE MANHOLE/LIFT STATION MATERIAL DIMENSIONS & PRICING


	Item	Description	Lifting Clutches Required (Ton)	Weight (kg/piece)
Large Diameter Manholes	1524 Diameter (C Wall Typical)	2440 High Barrel	4	5575
		914 High Barrel		2100
		305 High Barrel		700
		Top Slab/Base Slab		1925
	1829 Diameter (B Wall Typical)	2440 High Barrel	8	6850
		1829 High Barrel		5140
1220 High Barrel Top Slab/Base Slab		3425 2600/2725		
2130 Diameter (B Wall Typical)	2440 High Barrel Top Slab/Base Slab	8	9100 3525/3800	
2440 Diameter (C Wall Typical)	2440 High Barrel Top Slab/Base Slab	8	12775 4675/5175	
Concrete Boxes	2743 Diameter (C Wall)	2440 High Barrel	20	15800
		Top Slab/Base Slab	8	5950/6525
	3048 Diameter (B Wall)	2100 High Barrel	20	15350
		1220 High Barrel	8	8925
		610 High Barrel	8	4475
		Top Slab/Base Slab	8	7050/8000
Concrete Boxes	1200x600	2000 High Box Base Slab/Top Slab	4	3375 925 /1150
	1200x900	2000 High Box Base Slab/Top Slab	4	3750 1225/1500
	1800x1200	2000 High Box Base Slab/Top Slab	8	6450 2325/2800
	2400x1200	2000 High Box Base Slab/Top Slab	8	9250 3225/3750
	2400x1800	2000 High Box Base Slab/Top Slab	8	9825 4150/4400
	2440x2440	2440 High Box Base Slab/Top Slab	8	13375 5725/6400
	3000x2400	2000 High Box Base Slab/Top Slab	20 8	15650 7150/8100

1500 & 1800 Dia. Pre benched manholes available. Please call for pricing.


- NOTES:**
- Standard barrel and box heights shown. Monolithic base is available for custom heights.
 - Cored holes and rough openings available at an additional cost.
 - Oversized base slabs available to resist flotation in high ground water conditions. Please call for pricing.
 - Prices include rubber wedge gaskets and lube for large diameter round manholes only. Mastic gaskets are also available for box manhole joints. Additional measures may be needed if a watertight joint is required.
 - Top Slabs are typically 450 mm thick and base slabs are typically 300 mm thick; however the thickness may vary to suit engineering design.
 - 3 lifting clutches are required to lift all circular bases and top slabs, and 4 required for square/rectangular slabs. Circular bases and top slabs require 3 lifting clutches. Square/rectangular slabs require 4 lifting clutches.
 - 1500 and 1800 DIA. pre-bench manholes available. Please call for pricing.

BIG BOX MANHOLES & CONTROL STRUCTURES

Big box manholes are available for use as Type 1-5 manholes or lift stations. These sections are able to handle up to 3000mm diameter pipe. The Big Box size ranges from 2m, up to 6m with .5m increments in spans. The wall thicknesses are adjustable to 300 and 350mm thicknesses, and the joints are similar to those of a standard box section measuring 140mm in length.



Plan



Section

ASTM C1433



Adjustable form allows variations with 0.5m increments for square or rectangular manholes.

The adjustable wall thickness allow deep design.

Weir walls included in control structures.
Slide gates available as needed.
Via supply only.

BIG BOX MANHOLE - DIMENSIONS

Box Size Span x Rise	300mm Wall Thickness				350mm Wall Thickness				Haunch Dimension
	Base Slab/Top Slab Weight (kgs)	Weight of Section (kg)	Lifting Clutches (Ton)		Base Slab/Top Slab Weight (kgs)	Weight of Section (kg)	Lifting Clutches (Tons)		
3.0m x 2.5m	10650	8000	24000	20	11325	8525	28250	20	300
3.0m x 3.0m	12300	9500	25875	20	13000	10075	30450	20	300
3.0m x 3.5m	14050	10900	27750	20	14700	11600	32625	20	300
3.0m x 4.0m	15725	12375	29625	20	16400	13150	34825	20	300
3.5m x 3.5m	15925	12600	29625	20	16625	13375	34825	20	300
3.5m x 4.0m	17800	14325	31500	20	18525	15150	37000	20	300
4.0m x 4.0m	19900	16250	33375	20	20650	17125	39200	20	300

*For larger sizes please contact your Lafarge representative.

NOTES: 1. All weights are approximate and based on 2.5m section lengths.




MULTI PANEL VAULT



MULTI PANEL
VAULT

MULTI PANEL VAULT

For larger precast concrete underground structures, Lafarge offers custom designed multi panel vaults. This serves as a cost effective alternative solution to a cast in place structure.



Stormceptor®

(Oil / Grit Separator)

Stormceptor®MAX

The StormceptorMAX responds to the needs of large-scale industrial and residential areas which may require a single stormwater management device. It provides stormwater quality treatment for areas 10 to 100+ acres and industrial spill volume capture of 55,000+ litres.


One StormceptorMAX can provide protection for an entire neighbourhood, a full-scale industrial plant or other large developments.

Unique, comprehensive site coverage.

- Larger sedimentation chamber extends horizontally rather than vertically.
- Non-turbulent treatment environment allows oil to rise and sediment to settle.
- Industrial spill protection in dry and wet conditions.
- Patented scour prevention technology contains captured oil and sediment for safe storage and easy removal.



Stormceptor MAX installation.
A ten box Stormceptor MAX unit was used to treat 110 ha.
(5 boxes shown)



Stormceptor MAX installation. A nine box Stormceptor MAX.

Please call your local Lafarge Pipe representative for pricing based on individual project requirements.


Stormceptor® EF

The enhanced flow Stormceptor EF is a high performing oil grit separator that effectively removes and retains pollutants such as sediment (TSS), free oils, gross pollutants, nutrients and metals from stormwater and snowmelt runoff at higher flow rates than other oil grit separators

The Newest Oil Grit Separator (OGS) Stormwater Treatment Technology

Stormceptor® EF

- Improved TSS capture at higher flow rates
- Tested and verified through the ISO14034 ETV program



Stormceptor® EFO

- Captures and retains 99% of free hydrocarbons (oils)
- Ideal for gas stations, garages, and other oil hotspots



Easy to install

Small footprint saves time and money with limited disruption to your site.



Seamless

Minimal drop between inlet and outlet pipes makes Stormceptor ideal for retrofits and new development projects.



Flexible

Multiple inlets can connect to a single unit. Can be used as a bend structure.

Multiple configurations available to meet each project's specific needs



Single Inlet Inline

- Single inlet
- Allows 90 to 270 degrees between inlet and outlet



Multi-Inlet Inline

- Multiple inlets
- Allows 180 degrees between inlets



Grated Inlet


- Grated inlet
- Multiple inlet pipes
- Allows 90 degrees between inlet pipes



Submerged

- Handles submerged conditions up to 1.2 meters
- Single or multiple inlets

Stormceptor® EF (Enhanced Flow)




- Stormceptor EF is for standard applications
- Stormceptor EFO is specific for enhanced oil capture. An EFO is recommended for gas stations or parking lots

All Stormceptor EF/EFO models can accommodate

- Single Inlet
- Multiple Inlet
- Grate Inlet

Inlet to Outlet Drop

- 0° – 45°: The inlet pipe is 1-inch (25mm) higher than the outlet pipe.
- 45° – 90°: The inlet pipe is 2-inches (50mm) higher than the outlet pipe.



PRODUCT DETAILS

METRIC DIMENSIONS AND CAPACITIES								
Stormceptor Model	Inside Diameter	Minimum Surface to Outlet Invert Depth	Depth Below Outlet Pipe Invert	Wet Volume	Sediment Capacity ¹	Hydrocarbon Storage Capacity ²	Maximum Flow Rate into Lower Chamber ³	Peak Conveyance Flow Rate ⁴
	(m)	(mm)	(mm)	(L)	(m ³)	(L)	(L/s)	(L/s)
EF4 / EFO4	1.22	915	1524	1780	1.19	265	22.1 / 10.4	425
EF6 / EFO6	1.83	915	1930	5070	3.47	610	49.6 / 23.4	990
EF8 / EFO8	2.44	1219	2591	12090	8.78	1070	88.3 / 41.6	1700
EF10 / EFO10	3.05	1219	3251	23700	17.79	1670	138 / 65	2830

Jellyfish[®] Filter

Pollutant Removal

- TSS 85%
- Total Metals >50%
- Total Phosphorus 60%
- Turbidity <15 NTU
- Total Nitrogen 50%
- Trash 100%

LEED Credits

- Jellyfish filters can be used to achieve LEED credits
- NJDEP Certified for LEED credits

Pretreatment

- Traps oil, trash and debris outside the filtration zone.
- Coarse particles settle to the sump.
- Separator skirt protects the cartridge from floatables contamination.

Filtration

- Membrane filtration tentacles capture fine particles, as small as 2 microns.
- Removes a high percentage of particulate bound pollutants including nutrients, metals, hydrocarbons and bacteria.
- High surface area membranes ensure long lasting treatment.

Self-Cleaning Filters

- During filtration, vibrational pulses dislodge sediment from the membrane surfaces.
- After every storm peak, filtered water backwashes membrane filtration tentacles.
- Sediment is continuously removed from the tentacles by gravity.

Features

1. High surface area, high flow rate membrane filtration.
2. Highest treatment flow rate per cartridge (up to 80 gpm (5 L/s)).
3. Low head loss (typically 18 inches or less (457mm)).
4. Removes particles as small as 2 microns.
5. Light weight, self-cleaning cartridges.

Benefits

1. Long lasting and effective stormwater treatment.
2. Fewer cartridges required than other filtration systems, leading to a lower cost & easier maintenance.
3. Design is compatible with all piping systems.
4. Superior pollutant capture.
5. Easy maintenance & low life-cycle cost.



STORMTRAP[®] OPERATION

StormTrap[®] systems are available in two configurations to provide conventional detention, high early discharge or infiltration to groundwater.

SingleTrap[™] system

SingleTrap systems are made up of a single layer of modules. It can be founded on either a strip footing to create a large infiltrative surface area, or a conventional concrete slab for use as either a traditional detention basin, or a basin with high early discharge (refer to figure below). Water-tight options are available if required.

DoubleTrap[™] system

DoubleTrap systems are made up of two layers of precast pieces which together form one StormTrap module. The DoubleTrap system is founded on a compacted aggregate base and can be configured to provide infiltration of detained runoff to groundwater or conventional detention, either with or without high early discharge. Water-tight options are available if required.



A standard SingleTrap module and system



A standard DoubleTrap module and system

A Complete Solution

- Flexible footprint and design
- Reduced design time
- Maximum detention volume for the smallest footprint
- High infiltration capacity
- LEED & LID
- Full trafficability and reduced risk
- Cost savings
- Quick installation
- Full access and maintainability

STORMTRAP SYSTEM FOOTPRINT

Module Type	Dimensions	Comment
I, III and VI	2085 mm wide x 4270 mm long	Multiples of 2085 mm wide and 4270 mm long are the most cost effective.
II, IV, V and VII	2085 mm wide x 2135 mm long	

Storage Capacity (m ³)		50	100	150	200	300	400	500
SingleTrap System Footprint (meters)	Span	4.2	8.4	12.6	8.4	12.6	16.8	16.8
	Length	8.0	8.0	8.0	16.0	16.0	16.0	20.0
	Depth	1.5	1.5	1.5	1.5	1.5	1.5	1.5
DoubleTrap System Footprint (meters)	Span	2.1	4.2	6.3	8.4	6.3	8.4	8.4
	Length	8.0	8.0	8.0	8.0	16.0	16.0	20.0
	Depth	3.0	3.0	3.0	3.0	3.0	3.0	3.0

- NOTES:**
1. Maximum (typical) inside height is 1524mm for SingleTrap and 3048mm for DoubleTrap.
 2. Heights customizable to suit site conditions.



Standard Type I



Standard Type II



Standard Type III



Standard Type IV



Standard Type V



Standard Type VI



Standard Type VII

PERFORMANCE MONITORING PLAN

From Sale to Service

Lafarge offers a wide variety of stormwater solutions designed to meet your project needs, from StormTrap® detention and retention systems to our patented Stormceptor™ and Jellyfish™ technology. As part of our ongoing commitment to sustainability, Lafarge is now providing support services for ongoing operations and maintenance of our stormwater products.

All Stormceptor™, Jellyfish™, and StormTrap® systems offered by Lafarge now include a 5-year performance monitoring plan, including:

- Annual inspection for 5 years after installation
- Provided 5 Years Free Inspection, and quoting for Cleaning
- Cleaning service, if required, at an additional cost



Five Years Free Inspection and quoting for cleaning included



PERFORMANCE MONITORING PLAN

Benefits for Owners

- Annual inspections performed on a set schedule
- Effortless record management conforming to local regulations
- No cost for having the inspection performed
- Hassle-free service with no added coordination required
- No need to keep up with changing local regulations - Lafarge will address and inform owner of changes, as requires

Benefits for Municipalities

- Inspection and cleaning reports are automatically filed - no need to remind owners to submit them
- Provided technical support at installation
- Lafarge has the expertise to ensure all units are installed correctly and are functioning properly

Lafarge's performance monitoring plan takes the worry and effort out of maintaining your devices and helps to ensure compliance with local regulations. Our stormwater solutions team maintains the highest level of safety when performing services. Lafarge also provides support for installation of all cleaned operated Jellyfish filters.



Provided technical support at installation



3 year old Jellyfish filters after cleaning


@SOURCE-ENERGY GEOTHERMAL ENERGY CAPTURE CONCRETE PIPE

- **Industry leading Innovation!**

The @Source-Energy pipe system represents a major innovation in the concrete pipe industry that is focused around the concept of geothermal energy capture.


- **The @Source-Energy Pipe System:**

Heat energy is stored in the ground where it lies dormant and largely underutilized. The @Source-Energy pipe system functions as standard concrete pipe, with the added service of extracting heat energy from the effluent in the pipes and from the adjacent ground. Manufacture of @Source-Energy Pipe is similar to standard concrete pipe, except that a small diameter HDPE conduit, similar to a natural gas line, is wound throughout the core along with the steel reinforcement. This HDPE conduit is filled with a 30% ethanol/water blend that acts as a heat transfer fluid throughout the pipe system once installed.



The advantage of using @Source-Energy pipe is that as the storm and sanitary pipe needs to be installed as part of development, the incremental cost of the @Source-Energy component is relatively minimal. The mass of concrete, being a dense material, makes it an ideal casing for heat transfer to the ethanol/water conductive media. The result is an innovative, highly efficient system that uses 100% on-site renewable energy.


Geothermal Energy Recovery



STONE STRONG RETAINING WALL



There are Stone Strong blocks. Then there's everything else. With the biggest, best and most innovative precast block in the industry, Stone Strong Systems delivers fully and intelligently engineered retaining wall solutions that greatly reduce installation time and labor costs with unmatched safety, durability and aesthetics. State of the art? We go one better. This is state of the block.



21 foot tall Gravity Wall
Colorado Springs, CO

SOLID
Sheer size and weight provides structural strength without tie-backs

Available in four custom patterns and can be stained to match any colour



Fully engineered both structurally and geotechnically



DRAINAGE
Innovative, hollow design provides built-in drainage.



LIGHTER
Lighter weight makes jobs go faster, easier, at a lower cost.



BIGGER
Its 24-sq.-ft. size reduces labor costs and installation time.



INTERLOCKING
System designed to ensure blocks stay secure and level.

STONE STRONG RETAINING WALL



24 SF BLOCK

Face 8' x 3', Width 44"

The 24 SF Block contributes to the speed of installation. A small crew and a couple pieces of equipment can install 1,200 SF a day.



24-86

Face 8' x 3', Width 86"

Setting the standard for tall gravity walls. At 22.5,' it can go vertical with no tie-back.



24 SF MASS EXTENDER BLOCK

Face 8' x 3', Width 56"

The addition of the extender to the 24 SF Block provides for greater gravity wall heights.



6 SF BLOCK

Face 4' x 18", Width 44"

The 6 SF Block allows for tighter turning radius, wall steps at 18" increments and vertical and horizontal adjustments. Also includes a top block with recess.



6-28

Face 4' x 18", Width 28"

A perfect solution for smaller walls, get up to 60 pieces per truckload. Easy to move around on-site with a skid loader or mini-excavator.



24 SF TOP BLOCK

Face 8' x 3', Width 44"

The Top Block has an 8" recess at the top of the face to allow for multiple finish options.



3 SF BLOCK

Face 2' x 18", Width 44"

The 3 SF Block allows the wall to stay on running bond.



90° BLOCK

Face 4' x 18", Width 4'

The 90° Block provides for inside and outside 90° turns.



45° BLOCK

Face 4' x 18" x 8.25"

The 45° Block provides for inside and outside 45° turns.



DUAL FACE BLOCK

Face 8' x 18", Width 28"

The Dual Face Block provides for above-grade applications.



END / CORNER BLOCK

Face 4' x 18", Width 2'

The End / Corner Block is used for 90° turns and for end finish treatments.

HANDLING AND INSTALLATION GUIDELINE

Concrete Pipe Handling


Although each shipment of pipe is blocked and tied down by the hauler, inspect each pipe shipment upon arrival before unloading. Set aside damaged pipe and notify the pipe plant so that repair or replacement can be arranged. Damaged ends, chips or cracks that do not pass through the wall can usually be repaired. Provide padding between the pipe and lifting device to avoid damage during offloading. Stockpile pipe with all the bells arranged at the same end. If stacking pipe, each row should be arranged in the opposite direction with the spigot end protruding to keep the bells from resting on them. Ensure that the bottom row of stockpiled pipe is securely blocked at each end.

All flexible gasket materials, including joint lubricating compounds, should be stored in a cool dry place. Rubber gaskets and performed bulk mastics should be kept clean, away from oil, grease, excessive heat and out of the sun. Gaskets are made so that a precise volume of rubber is used from each joint, to provide long lasting, tight and flexible joint. O-ring gaskets for ASTM C76 & C361 pipe require a lubricant for proper installation. See “Gasket Installation” on the following page for gasket and lubrication procedures.

Do NOT transport pipe over uneven ground using lift anchors - this dynamic loading may cause damage to the lift anchor and concrete. Care must be taken not to tamper with lift pins. Tampering would include heating, hammering, welding, or side loading the pins or anything else that could damage the pin or concrete.

Keep the trench clean and dewatered with a firm bottom free of mud, taking care to prevent foreign material from entering the joint or pipe. Before the pipe is installed a bell hole must be dug in the bedding to accommodate the bell. Failure to do this can cause beam breaks or cracks in the barrel of the pipe.

During insertion of the spigot into the bell, before the pipe is homed, the pipe should be partially supported to minimize lateral pressure on the gasket and to maintain concentricity until the gasket is properly positioned. Once the bell and spigot have been carefully aligned, the pipe must be homed with a direct thrust and not moved from side to side as it enters the bell. Proper homing can be achieved as shown or with blocks and lever bars, or mechanical ‘come-alongs’ suitably braced to ensure even entry into the bell. Back hoes and tractors are NOT recommended for this purpose. If the bell and spigot are not carefully aligned, the gasket will be displaced causing a leak or splitting of the bell.




CONCRETE PIPE INSTALLATION PROCEDURES

- **Transporting, Lowering and Placing Pipe in Trench**

Pipe is laid into position using the Pipe Laying Sling in its symmetrical mode. They are lowered into the trench close to the previous pipe laid.

The pipe may be prevented from rolling laterally by partial backfilling.




- **Joining Pipe**

The long leg of the Pipe Laying Sling is attached to the farthest anchor on the previously laid pipe. The free leg is attached - out of the way - on the clevis link provided.

Locate the center of lift over the closest anchor of the previously laid pipe. This will properly align the direction of pull.

The pipe is pulled into position by slowly raising the boom on the crane or backhoe without moving the boom forward or backward.




- **Releasing the Load**

When the pipe has been pulled into position, the load is released and the Pipe Laying System is moved to the next pipe, and the process is repeated.

Warning: Anchors can become overloaded and fail if the crane or backhoe continues to apply load after the connection has been completed.


When handling precast concrete elements, extreme care should be taken to ensure that impact or dynamic loads are kept to a minimum. Impact or dynamic loads can greatly increase the applied load to the anchors.

Failure to observe the above warnings may lead to property damage, personnel injury and death.




GASKET INSTALLATION-PIPE


- Self-Lube Gasket



Carefully clean all dirt and foreign substances from the jointing surface of the bell or groove end of pipe.



Carefully clean spigot or tongue end of pipe, including the gasket recess.



Align bell and spigot of pipes to be jointed. Before homing the joint, check that the gasket is in contact with the entry taper around the entire circumference. Make sure pipe is aligned.


- Wedge Gasket




Carefully clean all dirt and foreign substances from the jointing surface of the bell or groove end of pipe.




Lubricate bell jointing surface liberally. Use a brush, cloth, sponge or gloves to cover entire inside surface. Only approved lubricant should be used.



Carefully clean spigot or tongue end of pipe, including the gasket recess.




Lubricate the spigot or tongue end of pipe, especially the gasket recess.







Lubricate the gasket thoroughly before it is placed on the spigot or tongue.

Fit the gasket carefully. Equalize the rubber gasket stretch by running a smooth, round object, inserted between gasket and spigot, around the entire circumference several times.




Align bell and spigot of pipes to be jointed. Before homing the joint, check that the gasket is in contact with the entry taper around the entire circumference. Make sure pipe is aligned.

- O-Ring Gasket




CATCHBASIN AND MANHOLE HANDLING

- Lifting Eye Installation




- How to Use the Universal Lifting Eye



NOTES: 1. Load must be applied simultaneous to all Swift Lift Anchors in order to safely lift product.

CATCHBASIN AND MANHOLE HANDLING

- Typical Applications




BOX CULVERT HANDLING

- **How to Handle and Set Concrete Box Sections**

As with lifting any concrete element, special care should be taken by the driver of the placement vehicle to ensure that the impact or dynamic loads are reduced to a minimum. Impact of dynamic loads can greatly overload the anchors and cause failure.

Load must be applied to all anchors simultaneously.




- **Correct Method for Pulling Box Sections Together**

To pull the box section into position, the long leg of the lift sling is coupled to the previously placed box section. The free short leg is hung into the hook provided for this purpose.

Ensure that the top guide pulley of the crane is over the outer lifting anchor of the previously placed box section so that the direction of pull is slightly inclined towards the placed box section.

Warning: The anchors can be overloaded and fail if the crane continues to pull on the sling after the connection is complete.



TERMS & CONDITIONS

1. All concrete products in this catalogue are manufactured using sulphate resistant cement - CSA A3000 Type HS.
2. Restocking/Cancelled order fee for undamaged stock material will be 15%.
3. Restocking/Cancelled order fee for damaged or unrepairable products may be up to 100%.
4. Restocking/Cancelled order fee for custom produced material may be up to 100%.
5. Prices effective January 2021, subject to change. Tax and freight NOT included.
6. Acceptance of terms: The purchaser agrees that the prices levied by Lafarge Canada Inc. for product/services take into consideration and are predicted on the purchaser assuming and releasing Lafarge Canada Inc. of certain liabilities and responsibilities by requesting product/services of Lafarge Canada Inc., the purchaser voluntarily elects to enter into this agreement and to be bound by all terms and conditions hereof rather than negotiate a different agreement which would execute the exculpatory indemnification, hold harmless and other provisions herein and wherein, such negotiated agreement would among other things involve substantially higher prices and/or require provisions of adequate insurance by and for the expense of the purchaser to protect Lafarge Canada Inc. against the liabilities and responsibilities assumed by the purchaser herein.
7. Lafarge Canada Inc. shall not be responsible for any direct or indirect damages whatsoever caused to the purchaser or otherwise by delays in deliveries, whether arising from fires, strikes, labour difficulties, material procurement difficulties, damage to plant or equipment, governmental regulations, accidents, transportation delays, or from any other cause whatsoever.
8. Orders will be accepted for reasonable color uniformity and finish of material. However, Lafarge Canada Inc. does not accept responsibility for exact shade duplication or finish.
9. Any production and delivery commitments made by Lafarge Canada Inc. are subject to the receipt by Lafarge Canada Inc. of all necessary information, details, and final approved drawings within the time specified.
10. Material will be delivered in full truck-load quantities as close to the job site as trucks of Lafarge Canada Inc. can reasonably proceed under their own power. Unloading time in excess of 1 hour will be charged by Lafarge Canada Inc. to the purchaser at prevailing rates.
11. The purchaser shall inspect all material at the time of delivery and mark any damage or shortage on the delivery ticket. The use or installation of material or the failure to notify Lafarge Canada Inc. of any defect within seven days after delivery will be deemed unconditional acceptance of the material and all obligations of Lafarge Canada Inc. with respect to such material shall thereupon terminate. The obligation of Lafarge Canada Inc. under this warranty is expressly limited to repairing or replacing defective material and the purchaser shall not have any claim for labour, other material or anything other than for such repair or replacement. This warranty is in lieu of all other warranties, expressed or implied, with respect to the material covered hereunder.
12. Lafarge Canada Inc. will not assume liability for any charge for defective materials or for alterations of defective materials, or for any work, except in cases where the prior written authorization of Lafarge Canada Inc. has been given.
13. All Clutches are considered as final sale and not returnable.
14. The purchaser shall assume responsibility for any dirt left on the street by Lafarge Canada Inc.'s trucks as a result of conditions at the place of delivery.
15. Terms of payment: Terms of payment rendered by Lafarge Canada Inc. are net cash within thirty (30) days from the date of invoice issuance, in Canadian dollars and in accordance with any payment instructions written on the invoice. If any invoice is not paid by the end of the said thirty (30) days, interest at the rate of two percent (2%) per month (26.8% per annum) shall be charged on all outstanding amounts. For unpaid amounts collected through legal proceedings or by a collection agency, the purchaser shall pay attorney and agency fees and reasonable costs thereof incurred by Lafarge Canada Inc. in addition to the amount of the invoice and any accrued interest.

Southern Alberta

2021

