

**SOLHYDCOAT SAFETY YELLOW**  
**- Part B****SECTION 1. IDENTIFICATION**

<b>Product Identifier</b>	SOLHYDCOAT SAFETY YELLOW -Part B
<b>Other Means of Identification</b>	SCOAT-YELLOW B
<b>Product Family</b>	Durcisseur -Partie B
<b>Recommended Use</b>	Epoxy Hardener for Injection resin.
<b>Restrictions on Use</b>	Use with Part A (resin) of this product.
<b>Manufacturer/Supplier Identifier</b>	BMQ SOLUTIONS, 1522 Boulevard des Laurentides, Laval, Qc, H7M 2N7, Marc Charlebois, 877-267-7249, <a href="http://www.lafarge.ca/en/bmq-solutions">www.lafarge.ca/en/bmq-solutions</a>
<b>Emergency Phone No.</b>	BMQ SOLUTIONS, 1522 Boulevard des Laurentides, Laval, Qc, H7M 2N7, Marc Charlebois, 877-267-7249, <a href="http://www.lafarge.ca/en/bmq-solutions">www.lafarge.ca/en/bmq-solutions</a>
<b>SDS No.</b>	00240014

**SECTION 2. HAZARD IDENTIFICATION**

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015).

**Classification**

Acute toxicity (Oral) - Category 5; Acute toxicity (Dermal) - Category 4; Acute toxicity (Inhalation) - Category 5; Skin corrosion - Category 1C; Serious eye damage - Category 1; Respiratory sensitization - Category 1B; Skin sensitization - Category 1

**Label Elements**

Signal Word:

Danger

Hazard Statement(s):

Causes skin irritation.

Causes severe skin burns and eye damage.

Harmful in contact with skin.

Harmful in contact with skin.

May be harmful if inhaled.

Causes serious eye damage.

May be harmful if swallowed.

Precautionary Statement(s):

Prevention:

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.

In case of inadequate ventilation wear respiratory protection (NIOSH approved air-purifying respirator with an organic vapour cartridge).

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Response:

---

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B

SDS No.: 00240014

Page 01 of 06

Date of Preparation: février 22, 2016

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, regional, national and international regulations.

#### **Other Hazards**

May be a health hazard in confined spaces.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Isophorone diamine	2855-13-2	40-60	
4-Nonylphenol, branched (mixed isomers)	84852-15-3	33-45	
Benzyl alcohol	100-51-6	15-25	

### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

##### **Inhalation**

Move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Call a Poison Centre or doctor if you feel unwell.

##### **Skin Contact**

Avoid direct contact. Wear chemical protective clothing if necessary. Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely. If skin irritation or a rash occurs, get medical advice or attention.

##### **Eye Contact**

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

##### **Ingestion**

DO NOT INDUCE VOMITING get medical advice or attention if you feel unwell or are concerned. Have victim drink water or milk, if conscious.

##### **First-aid Comments**

Get medical advice or attention if you feel unwell or are concerned.

#### **Most Important Symptoms and Effects, Acute and Delayed**

If in eyes: can cause effects as described for skin contact. The vapour also irritates or burns the skin. Permanent scarring can result. If on skin: repeated or prolonged exposure can irritate the skin. If inhaled: may cause moderate to severe irritation.

#### **Immediate Medical Attention and Special Treatment**

##### **Target Organs**

Eyes, skin, respiratory system, digestive system.

##### **Special Instructions**

Not applicable.

##### **Medical Conditions Aggravated by Exposure**

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B

SDS No.: 00240014

Page 02 of 06

Date of Preparation: février 22, 2016

Eye conditions, respiratory conditions, asthma. May cause skin sensitization.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog. Use water to keep non-leaking, fire-exposed containers cool.

#### Unsuitable Extinguishing Media

Not applicable.

### Specific Hazards Arising from the Product

May accumulate in hazardous amounts at ceilings and at the top of confined spaces, resulting in a health hazard. Heating increases the release of toxic vapour.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide; corrosive phenols.

### Special Protective Equipment and Precautions for Fire-fighters

Approach fire from upwind to avoid hazardous vapours or gases. Before entry, especially into confined areas, use an appropriate monitor to check for: toxic gases or vapours.

Fire-fighters should enter area wearing specialized protective equipment. (Bunker Gear will not provide adequate protection.).

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel.

### Environmental Precautions

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Minimize the use of water to prevent environmental contamination.

### Methods and Materials for Containment and Cleaning Up

Small spills or leaks: contain and soak up spill with absorbent that does not react with spilled product. Contaminated absorbent poses the same hazard as the spilled product. Large spills or leaks: collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Review Section 13 (Disposal Considerations) of this safety data sheet.

### Other Information

Report spills to local health, safety and environmental authorities, as required.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Do not get in eyes, on skin or on clothing. Wear personal protective equipment to avoid direct contact with this chemical. Avoid generating vapours or mists. Do not swallow. Wash hands thoroughly after handling this material. Use adequate ventilation and employ respiratory protection where dust or fumes may be generated.

### Conditions for Safe Storage

Concentrated product: store in an area that is: ventilated, cool.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B  
SDS No.: 00240014  
Date of Preparation: février 22, 2016

## Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Benzyl alcohol	10 ppm					

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average.

### Appropriate Engineering Controls

Concentrated product: general ventilation is usually adequate. Provide eyewash in work area, if contact or splash hazard exists. Breathing Vapours must be avoided.

### Individual Protection Measures

#### Eye/Face Protection

Wear chemical safety goggles.

#### Skin Protection

Concentrated product: wear chemical protective clothing e.g. gloves, aprons, boots.

#### Respiratory Protection

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

Appearance	Clear yellow.
Odour	Ammonia-like
Initial Boiling Point/Range	> 120 °C (248 °F)
Vapour Pressure	0.05 mm Hg (0.01 kPa)
Relative Density (water = 1)	1.00 at 25 °C

### Other Information

Physical State	Liquid
----------------	--------

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Controlled polymerizations when mixed with the part A of this material.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

Reacts in the presence of heat. See "Hazardous Decomposition Products".

### Conditions to Avoid

Prolonged exposure to high temperatures.

### Incompatible Materials

Highly reactive. Oxidizing agents (e.g. peroxides), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

### Hazardous Decomposition Products

When exposed to very high temperatures will release very toxic carbon monoxide, carbon dioxide; corrosive phenols.

## SECTION 11. TOXICOLOGICAL INFORMATION

Corrosive liquid information presented below is for the entire product, unless otherwise specified.

### Likely Routes of Exposure

Skin contact; eye contact; inhalation; ingestion.

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B

SDS No.: 00240014

Date of Preparation: février 22, 2016

## Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Benzyl alcohol	> 1000 mg/L (rat) (4-hour exposure) (vapour)	1360 mg/kg (mouse)	2000 mg/kg (rabbit)
Isophorone diamine		1030 mg/kg (rat) (4-hour exposure)	1840 mg/kg (rabbit) (4-hour exposure)

### Skin Corrosion/Irritation

Repeated or prolonged exposure can irritate or burn the skin.

### Serious Eye Damage/Irritation

Symptoms include sore, red eyes, and tearing.

### STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May be harmful nose and throat irritation.

#### Skin Absorption

May be harmful can cause sensitization.

#### Ingestion

May be harmful Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

### Aspiration Hazard

Not known to be an aspiration hazard.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure

Conclusions cannot be drawn from the limited studies available.

### Respiratory and/or Skin Sensitization

Human experience shows severe asthma or asthma-like symptoms (respiratory sensitization) in rare cases following exposure at work. Skin sensitizer.

No information was located for: STOT (Specific Target Organ Toxicity) - Single Exposure, Aspiration Hazard, STOT (Specific Target Organ Toxicity) - Repeated Exposure, Development of Offspring, Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

## SECTION 12. ECOLOGICAL INFORMATION

Not hazardous to the environment.

### Ecotoxicity

Studies were not located.

#### Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Benzyl alcohol	10 mg/L (Lepomis macrochirus (bluegill); 96-hour)			

### Persistence and Degradability

Considered not to degrade rapidly, because no data regarding degradability are available.

### Bioaccumulative Potential

No information was located.

### Mobility in Soil

No information was located.

### Other Adverse Effects

There is no information available.

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B

SDS No.: 00240014

Date of Preparation: février 22, 2016

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal Methods

The required hazard evaluation of the waste and compliance with the applicable hazardous waste laws are the responsibility of the user.

## SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1760	Corrosive liquid N.O.S. ((Triethylenetetramine))	8	II

**Special Precautions** Not applicable

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## SECTION 15. REGULATORY INFORMATION

### Safety, Health and Environmental Regulations

#### Canada

#### Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL or are not required to be listed.

## SECTION 16. OTHER INFORMATION

**NFPA Rating** Health - 3 Flammability - 0

**SDS Prepared By** BMQ SOLUTIONS

**Phone No.** 877-267-7249

**Date of Preparation** février 22, 2016

**Date of Last Revision** janvier 18, 2016

**Key to Abbreviations** ACGIH® = American Conference of Governmental Industrial Hygienists

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

OSHA = US Occupational Safety and Health Administration

**References** CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

**Disclaimer** We declare the information contained herein are correct. However, we decline all responsibility as to the exactness and the usage of the later.

Product Identifier: SOLHYDCOAT SAFETY YELLOW -Part B

SDS No.: 00240014

Page 06 of 06

Date of Preparation: février 22, 2016