



SOLHYDGRROUT CABLE

High-resistance, pumpable, non-shrink grout providing corrosion protection for anchors and cables.

SOLHYDGRROUT CABLE is a high-performance, shrinkage-compensated, pumpable grout designed for anchoring cables, rods, and bolts. Its advanced formulation ensures high fluidity, excellent mechanical bonding, and superior protection against corrosion. It resists water washout, making it ideal for applications in wet or challenging environments. Once cured, it exhibits a dense, concrete-like finish with exceptional durability.

■ USES

SOLHYDGRROUT CABLE is designed for precision grouting applications requiring fluid consistency, non-shrink properties, and high durability.

TYPICAL USES:

- Cable bolting in tunneling and mining
- Grouting of anchor rods, bars, cables, or bolts in soil or rock media
- Injection of narrow, confined spaces
- Structural grout medium for micropiles
- Earth tie-backs for excavation and soil stabilization
- Filling of pipe piles and post-grouting of micropile installations
- Grouting support systems in tunnelings

■ PRODUCT FEATURES

- High fluidity for easy placement and pumpability
- Thixotropic properties reduce material loss in fractured ground
- Shrinkage compensated to ensure long-term stability
- Resistant to water washout, ensuring reliable performance in wet conditions
- Reduced bleeding, maintaining consistency during curing
- Low permeability, enhancing durability and resistance to environmental factors
- Superior resistance to sulfate attack, extending service life

■ SURFACE PREPARATION

All surfaces in contact with SOLHYDGRROUT CABLE must be free of oil, grease, laitance, and contaminants. Roughen the surface to ensure proper adhesion and clean thoroughly with water until saturated but free of standing water.

■ PRIMING

No primer required.

■ PRODUCT MIXING

- SOLHYDGRROUT CABLE must be vigorously mixed using a high-shear mixer, such as a high speed drill mixer cable of reaching 2000 RPM or equivalent for a minimum of 3 minutes or until a smooth, homogeneous blend is obtained.

■ PRODUCT APPLICATION

When formwork is required, it must be firmly anchored and watertight.

PLACING

SOLHYDGRROUT CABLE can be poured into place or pumped.

■ CURING

Allow any grout exposed to a water cure for 24 hours.

■ ESTIMATING / YIELD

SOLHYDGRROUT CABLE is offered in 22.7 kg (50 lbs) bags and provides 0.015 m³ (0.54 ft³) of fluid grout when mixed with 7.5 liters of potable water.

MATERIAL PHYSICAL PROPERTIES

COMPRESSIVE STRENGTH ASTM C-109 cube 50mm x 50mm			FRESH GROUT PROPERTIES ASTM C-930	
Freshly Mixed Temperature	23°C	74°F	Freshly Mixed Temperature	23°C (74°F)
Curing Temperature	23°C	74°F	% Bleeding	0%
7 days	45 MPa	(6,525 psi)	% Combined Expansion	3-6%
28 days	60 MPa	(8,700 psi)	% Segregation	0%
FLOW CONE ASTM C-939				
Freshly Mixed Temperature			23°C (74°F)	
Flow			20-30 seconds	



SOLHYDGROUT CABLE

High-resistance, pumpable, non-shrink grout
providing corrosion protection for anchors and cables.

■ PRECAUTIONS / RESTRICTIONS

- Tools and equipment must be cleaned with water before the product hardened
- Only add chemical admixtures or thinners approved or directed by BMQ Solutions
- Use water quantity as specified in this document
- Store materials in a dry place
- The application temperature must be 4° C or more and remain so for 24 hours after application
- Use cold or hot weather grouting best practices when applicable
- Strength gain and setting time are significantly influenced by extreme temperatures
- BMQ Solutions is not responsible for corrosion caused by ingredients in the washing, saturation or mixing water, or for contaminants contained in the spaces to be injected or coming from materials used in the grouting application
- In order to minimize bleeding in vertical applications over 6.1 m (20 ft), BMQ Solutions recommends a dosage of water of no more than 5.7 liters per 22.7kg
- Always consult safety data sheet before use

■ PACKAGING

SOLHYDGROUT CABLE :

Bags 22.7 kg (50 lbs)
Qty: 56 bags per pallet

■ RECOMMENDED TOOLS

The following tools will assure a cost effective, satisfactory installation:

- Power drill with "Jiffy" type mixer
- Magnesium or Steel trowel
- Flow Cone
- Grout pump for large volume applications

■ CLEANING

Use water to clean all tools immediately after use.

■ STORAGE

Store in cool dry heated area on skids avoiding all moisture.
Can be kept in unopened bags for 18 months.

■ SAFETY

See Material Safety Data Sheet.

Contains Portland cement and silica sand. May irritate eyes and skin. Avoid contact with eyes or prolonged contact with skin. In case of contact, flush thoroughly with water. Avoid breathing dust.

BMQ SOLUTIONS WARRANTS that the product conforms to its chemical description and is reasonably fit for the purpose stated on its Technical Data Sheet when used in accordance with its directions. BMQ Solutions makes NO OTHER WARRANTY either expressed or implied.
Buyer assumes all risk in handling.

For Professional Use Only