

**STRUCTUROC E.T****SECTION 1. IDENTIFICATION**

<b>Product Identifier</b>	STRUCTUROC E.T
<b>Other Means of Identification</b>	SOL-ROC-E.T
<b>Recommended Use</b>	Quick setting cement repair mortar.
<b>Manufacturer/Supplier Identifier</b>	BMQ SOLUTIONS, 1522 Boulevard des Laurentides, Laval, Qc, H7M 2N7, Marc Charlebois, 877-267-7249, <a href="http://www.lafarge.ca/en/bmq-solutions">www.lafarge.ca/en/bmq-solutions</a>
<b>Supplier Identifier</b>	BMQ SOLUTIONS, 1522 Boulevard des Laurentides, Laval, Qc, H7M 2N7, Marc Charlebois, 877-267-7249, <a href="http://www.lafarge.ca/en/bmq-solutions">www.lafarge.ca/en/bmq-solutions</a>
<b>Emergency Phone No.</b>	Marc Charlebois, 514-705-7198, 24 Heures / 7 Jours CANUTEC, 613-996-6666, 24HR/7Jours
<b>SDS No.</b>	0189
<b>Date of Preparation</b>	mai 13, 2016

**SECTION 2. HAZARD IDENTIFICATION**

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015).

**Classification**

Acute toxicity (Oral) - Category 4; Skin irritation - Category 2; Serious eye damage - Category 1; Respiratory sensitization - Category 1; Skin sensitization - Category 1; Carcinogenicity - Category 1A; Reproductive toxicity - Category 1B; Specific target organ toxicity (single exposure) - Category 3; Specific target organ toxicity (repeated exposure) - Category 1

**Label Elements**

Danger

Hazard Statement(s):

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

May cause respiratory irritation.

Prevention:

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Response:

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Rinse mouth.

---

Product Identifier:	STRUCTUROC E.T
SDS No.:	0189
Date of Preparation:	mai 13, 2016

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTRE or doctor.

IF ON SKIN: Wash with plenty of water/

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice or attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, regional, national and international regulations.

#### Other Hazards

Contains ingredients -in there powdered form -that are suspected of cancer caused by overexpose to the dust and Respirable fractions.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Silica, quartz	14808-60-7	<65	
Portland cement	65997-15-1	<55	
Cement, alumina, chemicals	65997-16-2	<22	
Calcium sulfate, anhydrous	7778-18-9	<7	

### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

##### Inhalation

Move to fresh air. Can cause respiratory irritation or lung damage get medical advice or attention if you feel unwell.

##### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. If exposed or concerned, get medical advice or attention. For severe exposures get under safety shower after having removed clothing.

Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

##### Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice or attention. Seek medical attention for abrasion and burns.

##### Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Have victim drink several glasses of water, if conscious get medical advice or attention if you feel unwell or are concerned. If vomiting occurs naturally, keep head below hips to prevent aspiration of liquid into lungs and have person drink plenty of water. Immediately call a Poison Centre or doctor. Specific treatment is required.

#### Most Important Symptoms and Effects, Acute and Delayed

If in eyes: can cause thermal burns from heat released when it reacts with water. Symptoms include pain, redness, and swelling. If on skin: may cause skin and eye irritation. May cause burns in presence of moisture do not allow product to harden or have prolonged contact with skin or around body parts if inhaled: may cause respiratory irritation could severely damage lung tissue.

#### Immediate Medical Attention and Special Treatment

##### Target Organs

Respiratory system, eyes, skin.

##### Special Instructions

Symptoms may not appear immediately.

Product Identifier: STRUCTUROC E.T

SDS No.: 0189

Date of Preparation: mai 13, 2016

## Medical Conditions Aggravated by Exposure

Respiratory conditions, skin conditions.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

#### Unsuitable Extinguishing Media

None known.

### Specific Hazards Arising from the Product

This product presents no unusual hazards in a fire situation.

Not known to generate any hazardous decomposition products in a fire. may include but not limited to Carbon oxides.

### Special Protective Equipment and Precautions for Fire-fighters

Approach fire from upwind to avoid hazardous vapours or gases.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Allow the product to dry and harden. Avoid generating dust use the personal protective equipment recommended in Section 8 of this safety data sheet. Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel.

### Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. Minimize the use of water to prevent environmental contamination.

### Methods and Materials for Containment and Cleaning Up

Do not direct water at spill or source. Avoid generating dust. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up. Small spills or leaks: collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Large spills or leaks: dike spilled product to prevent runoff. Get expert advice before treating the spilled product with other chemicals to make it less hazardous. Remove or recover liquid using pumps or vacuum equipment.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Avoid generating dusts. Use adequate ventilation and employ respiratory protection where dust or fumes may be generated avoid repeated or prolonged skin contact. Do not get in eyes. Do not use compressed air for cleaning clothing or equipment, etc. Launder clothes before rewearing. Inform laundry personnel of product hazard(s). Avoid high ambient temperatures and humidity.

### Conditions for Safe Storage

Protect from conditions listed in Conditions to Avoid in Section 10 (Stability and Reactivity). Store in the original, labelled, shipping container. Avoid dust build up keep the container away from moisture.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Silica, quartz	0.025 mg/m <sup>3</sup> A2 RSEN		0.1 mg/m <sup>3</sup>			
Portland cement	1 mg/m <sup>3</sup> (E) RSEN		15 mg/m <sup>3</sup> (E) RSEN			
Cement, alumina, chemicals	10 mg/m <sup>3</sup>		15 mg/m <sup>3</sup>			
Calcium sulfate, anhydrous	10 mg/m <sup>3</sup>			15 mg/m <sup>3</sup>		

### Appropriate Engineering Controls

Product Identifier: STRUCTUROC E.T  
SDS No.: 0189  
Date of Preparation: mai 13, 2016

Avoid breathing dust keep exposure levels below the exposure limits use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Provide eyewash and safety shower if contact or splash hazard exists. Keep exposure levels below the exposure limits.

#### Individual Protection Measures

##### Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

##### Skin Protection

Wear suitable waterproof gloves wear chemical protective clothing e.g. gloves, aprons, boots.

##### Respiratory Protection

Wear a NIOSH approved particulate respiratory equipped with an N95, R95, or P95 filter. When ventilation is inadequate wear a NIOSH approved air-purifying respirator with N100, R100, or P100 filter(s).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

Appearance	Dark grey - brown fine powder.
Odour	Not available
Odour Threshold	Not available
pH	10.5 - 11.5
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	Not applicable
Evaporation Rate	Not applicable
Flammability (solid, gas)	Will not burn.
Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)
Vapour Pressure	Not applicable
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	2.7 - 3.0 at 20 °C
Solubility	Slightly soluble in water; Insoluble in ketones (e.g. acetone).
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not available
Other Information	
Physical State	Solid

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use. Will react in presence of water- Will heat up and harden.

### Chemical Stability

Normally stable. Keep in a dry storage area.

### Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

### Conditions to Avoid

Water, moisture or humidity.

### Hazardous Decomposition Products

May include ,and are not limited to: oxides of carbon.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Inhalation; skin contact; skin absorption; eye contact; ingestion.

### Acute Toxicity

---

Product Identifier:           STRUCTUROC E.T  
SDS No.:                       0189  
Date of Preparation:       mai 13, 2016

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Silica, quartz		500 mg/kg (rat) (dust)	

#### Skin Corrosion/Irritation

May cause moderate or severe irritation based on information for closely related materials. May cause moderate or severe irritation based on information for closely related materials. May burn the skin. Permanent scarring may result.

#### Serious Eye Damage/Irritation

May cause serious eye damage based on information for closely related materials. Symptoms include sore, red eyes, and tearing.

#### STOT (Specific Target Organ Toxicity) - Single Exposure

##### Inhalation

May cause respiratory tract irritation severe lung injury. Symptoms include burning, sneezing and coughing may cause serious lung disease acute silicosis symptoms shortness of breath, fever, cough and weight loss, could cause death.

##### Skin Absorption

Symptoms may include redness, rash, swelling and itching. Thermal burns from heat released when it reacts with water. Can cause sensitization.

##### Ingestion

May cause irritation of the mouth, throat and stomach. Symptoms may include nausea, vomiting, stomach cramps and diarrhea.

#### STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause irritation of the respiratory system. Respiratory tract injury has been observed. Lung disease silicosis.

#### Respiratory and/or Skin Sensitization

Human experience shows an allergic skin reaction (skin sensitization) in rare cases following exposure at work.

#### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Silica, quartz	Group 1	A2		
Portland cement		A4		

May cause cancer based on information for closely related chemicals. Known to cause: lung cancer. Excessive inhalation of Respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called Silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function.

#### Reproductive Toxicity

##### Development of Offspring

Conclusions cannot be drawn from the limited studies available.

##### Sexual Function and Fertility

Conclusions cannot be drawn from the limited studies available.

##### Effects on or via Lactation

No information was located.

## SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No information was located. May cause long term adverse effects in aquatic environment.

#### Persistence and Degradability

Expected not to degrade rapidly based on indirect evidence e.g. knowledge from structurally similar substances.

#### Bioaccumulative Potential

No information was located.

#### Mobility in Soil

No information was located.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

## SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations.

**Special Precautions** Not applicable

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## SECTION 15. REGULATORY INFORMATION

### Safety, Health and Environmental Regulations

This product has been classified in accordance with hazard criteria of the Controlled products regulations and this SDS contains all information required by the Controlled Products Regulations.

#### Canada

#### WHMIS 1988 Classification



Class D2A; D2B

Class E

D2A - Very Toxic (Chronic toxicity); D2B - Toxic (Skin irritant; Eye irritant); E - Corrosive

## SECTION 16. OTHER INFORMATION

**NFPA Rating**

**Health - 1**

**Flammability - 0**

**Instability - 0**

**SDS Prepared By**

BMQ SOLUTIONS

**Phone No.**

877-276-7249

**Date of Preparation**

mai 13, 2016

**Date of Last Revision**

juin 30, 2016

**Key to Abbreviations**

ACGIH® = American Conference of Governmental Industrial Hygienists

AIHA® = AIHA® Guideline Foundation. OSHA = US Occupational Safety and Health Administration

**References**

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

**Disclaimer**

We declare the information contained herein are correct. However, we decline all responsibility as to the exactness and the usage of the later.

Product Identifier: STRUCTUROC E.T

SDS No.: 0189

Date of Preparation: mai 13, 2016

Page 06 of 06