

SOLHYDFLOW EMULSION

High performance acrylic emulsion,
bonding agent and additive

SOLHYDFLOW EMULSION is a water-based, high solid acrylic emulsifier that is used to improve the adhesion of SOLYDROC cementitious products to the different substrates to which they are applied. Even when exposed to moisture, SOLYDFLOW EMULSION remains highly effective, making it ideal for indoor and outdoor applications.

USE

Use SOLHYDFLOW EMULSION has indicated with cementitious patching compounds, self-leveling agents, mortars, and SOLHYDROC repair concrete in order to improve: the adhesion properties, the flexion and tensile properties when required and has needed.

Modified materials will also have: a better resistance to abrasion, to moisture and better resistance properties to water, freeze/thaw and cracking.

PRODUCT FEATURES

- Can be used for many types of applications
- Improve resistance to moisture and freeze/thaw
- Concentrated liquid and high solid content
- Can be used as a bounding agent or mixed with water
- Water-based product; non-flammable, non-toxic and non-explosive

- Improve the adherence, strength and flexibility
- Without nocive vapors or gaseous emissions. Meets VOC standards.
- Increase the working time of the product to which it is added
- Use indoor or outdoor, above and below the ground
- Extra fine particles for a better product penetration

SURFACE PREPARATION

Must comply with the specific instruction of surface preparation according to the SOLHYDROC product applied. All surfaces must be ceaned to remove all traced of dirt, dust, mold, slat, grease, oil asphalt, laitance, curing compounds, paint, coating and any other foreign materials. All of those should be remain by mechanical means. Acceptable surface cleaning method included shot-blasting, sand-blasting, water-blasting and any others similars means. Sandblasting must be made on approved wood surface only. Never apply acid or chemical cleaner on surface that will receive SOLHYDROC products. New concrete surfaces must be allowed to cure a minimum of 28 days.

ESTIMATE AND EFFIENCY

Wood substrate:

Undiluted: 200 à 250 pi²

Standard Concrete:

Diluted 1: 1 300 à 400 pi²

Additive dilution ratio: Refer to the technica data sheet of your choosen SOLHYDROC product for any dilution or application method. Undiluted SOLYDFLOW EMULSION with clean water (1 for 1), SOLHYDFLOW EMULSION diluted with clean water (3 for 3).

PHYSICAL PROPERTIES

INFLAMMABILITY ASTM E-84

Flame Spread	0
Fuel Supply	0
Smoke release	0

APPLICATION

Temperature Range	10°C à 35°C (50°F et 95°F)
Drying Time	1 to 2 hours
Open Time	until 24 hours
Lifetime	1 year (original package)
Color	White

SOLHYDFLOW EMULSION

High performance acrylic emulsion,
bonding agent and additive

■ PRODUCT MIXING

Always be sure to mix properly SOLHYDFLOW EMULSION before using it. If necessary dilute SOLHYDFLOW EMULSION with clean cold water. Mix the indicated ration as indicated on the data product sheet.

■ PRODUCT APPLICATION

Additive

Measure and add the appropriate amount of water to the mixture into a clean container, then add the SOLHYDROC cementitious product while constantly mixing. follow all the instruction about mixing and application related to your SOLHYDROC product.

Bonding Agent

Use as indicated on the SOLHYDROC data sheet for cement based product.

Approved wood substrate (interior only)

Apply a thin layer using the 5mm roller (1/4 "). Do not leave any extra uncovered surface. Allow it to dry, it must remains sticky (maximum of 12 hours).

Standard porous concrete

Dilute the product (1 for 1 ratiore) with clean water and apply it on the surface with a broom or a brush. Do not leaver uncovered area. Allow it to dry, it must remains sticky (maximum of 8 hours).

■ CONDITIONING

Sceal : 18,9 L (5 gal US)
Bottle : 3,78 L (1 gal US)
Quantity : 4 bottles per box

■ RECOMMENDED TOOLS

The following tools will ensure efficient and economical installation :

- Broom or brush
- Roller 5mm (1/4")

■ CLEANING

Use water to clean tools immediately after using them

■ STORAGE

Keep the product in a dry place between 10°C et 30°C (50°F and 86°F). Évavoid freezing.

■ SECURITY

See the safety sheet.

SOLHYDROC INC. GARANTIT la qualité de ses produits. Ceux-ci sont conformes à la description donnée dans les fiches techniques, sur les étiquettes et sont appropriés à l'usage auquel ils sont destinés. Solhydroc Inc. n'exerce aucun contrôle sur les conditions de chantiers, les méthodes d'utilisation et les conditions d'emploi. La garantie de Solhydroc couvre uniquement la haute qualité de ses produits.

Produit pour usage professionnel

www.solhydroc.com